

Fact Sheet

Recovery Manager Hardware

Perfect clear overview



SefrinTec Recovery Manager software, pre-installed on a ruggedized 11.6" tablet gives you a clear overview of the entire recovery operation.



GETAC F110 FULLY RUGGED 11.6" TABLET

Large 11.6" LumiBond® sunlight readable display 4th generation Intel® Core™ processor

Dual hot-swappable battery design

Optional integrated 4G LTE broadband wireless 802.11ac next generation WiFi

Optional 1D/2D imager barcode reader

Intel HD graphics 4400

MIL-STD 810G and IP65 certified

Industry-leading bumper-to-bumper warranty

Fact Sheet

Recovery Manager Hardware

Technical specifications

Operating System	- Windows® 7 Professional - Windows 8 Professional
CPU	- Intel® Core™ i7-4600U 2.1 GHz processor with Turbo Boost Technology up to 3.3GHz 4MB L3 Intel Smart Cache - Intel Core i5-4300U 1.9 GHz processor with Turbo Boost Technology up to 2.9 GHz 3MB L3 Intel Smart Cache
Storage and memory	- Solid State 128GB / 256GB ⁶ - 4GB DDR3 expandable to 8GB ³
VGA controller	- Intel HD Graphics 4400
Display	- 11.6" TFT LCD HD (1366x768) 800 NITS LumiBond® sunlight readable LED display with multi-touch technology
Rugged features	- MIL-STD 810G and IP65 certified - MIL-STD 461F ready ² - Optional ANSI/ISA 12.12.01 - Vibration & drop resistant
Interface	- DC in x 1 - USB 3.0 x 1 - Docking port x 1 - Headphone out/Mic-in Combo x 1 HDMI x 1 - Optional RF antenna pass-through for GPS, WLAN and WWAN
Communications	- Intel Dual Band Wireless-AC 7260 (802.11ac) - Bluetooth (v4.0 class 1) - Optional SiRFstarIVTM GPS - Optional 4G LTE mobile broadband
Power	- AC Adapter (65 W, 100-240 VAC, 50/60 Hz) - Hot swappable Dual Li-Ion battery (2160 mAh) x 2 (up to 12.4 hours of battery life) ⁵
Warranty	- 3 Year bumper-to-bumper warranty standard ⁸
Dimensions and weight	- 12.3" x 8.15" x 0.96" (314 x 207 x 24.5 mm) - 3.08 lbs (1.4 kg) ⁷
Temperature	- Operating Temp: -6° F to 140° F / -21° C to 60° C - Storage Temp: -40° F to 160° F / -40° C to 71° C - Humidity: 95% RH, non-condensing

Technical specifications

Integrated options ⁴	- 1D/2D imager barcode reader; - or RS232 Port; or - 10/100/1000 base-T Ethernet; - or MicroSD slot; or - USB 2.0 port - Optional HD webcam x 1 - Optional 5MP auto focus camera
Security	- Intel vPro™ technology - TPM 1.2 - Cable lock slot - NIST BIOS compliant - Optional 13.56 MHz RFID - Optional contactless smart card reader
Keyboard	- Six tablet buttons: Power, Menu, Programmable, Camera Capture/Barcode Reader Trigger, Volume Up and Volume Down

Specification subject to change without notice.

¹ Data plan required. Cellular data is available in the US on Verizon Wireless and AT&T networks. LTE is available in select markets. Check with your carrier for details. 4G LTE configuration must be ordered at time of purchase.

² Requires MIL-STD 461F 90W AC Adapter sold separately.

³ Computers configured with a 32-bit operating system can address up to 3GB of system memory. Only computers configured with a 64-bit operating system can address 4 GB or more of system memory.

⁴ Expansion slot factory installed and limited to one option. Subject to minimum purchase requirements.

⁵ Battery life testing conducted under BatteryMark 4.0.1. Battery performance will vary based on software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. As with all batteries, maximum capacity decreases with time and use and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings.

⁶ For storage, 1GB = 1 billion bytes; actual formatted capacity less.

⁷ Weight varies by configuration and manufacturing process.

⁸ 3 year bumper-to-bumper limited warranty standard. For warranty terms and conditions visit www.getac.com